



Advanced Marine Decking

24 Cooperage Green
Royal Clarence Yard
Weevil Lane
Gosport PO12 1AX

Technical Information

Plank Widths Available:	45mm & 75mm, with caulking and join. 60mm & 75mm margin board, caulking to one side only 125mm king plank, no caulking or join. Available with Black or Ivory caulking
Thickness:	5.5 mm
Coil Lengths (1 sq. mt.):	45mm – 22 meters 60mm – 16.5 meters 75mm – 13 meters 125mm – 8 meters
Material:	Filled flexible PVC extrusion compound with good UV stability and outdoor grade pigments.
Specification:	BS 7655 T11, T12, TM1, TM2 and Type 9
Specific Gravity:	1.4
Water Absorption:	0.08 %
Shore “A” Hardness:	40 shore D
Weight:	6 kg per square meter
UV Resistance:	Laboratory tests after equivalent of 5 years exposure to high intensity UV light indicates slight darkening of colour.
Adhesives:	Plank to Plank: Quick cure clear PVC resin/solvent base adhesive. Plank to Deck: Two part polyurethane adhesive. Pot life 30 – 60 mins. Formulated for bonding PVC to various substrates including GRP, wood and metal. depending on temperature. Full cure time 4 – 6 hours.
Caulking:	Black MS Polymer based all purpose seam sealer with excellent adhesion to all types of material

Uk Distributors of

FLEXITEEK

E mail: technical@advancedmarinedecking.co.uk
Tel: 02392 529966 Fax: 0870 762 7024